

Humidity & Temperature Meter ET-931



FEATURES

- ▶ °C/°F selection
- ▶ MAX/MIN record
- ▶ Data Hold
- ▶ Dew Point Measuring
- ▶ Auto Power Off Setting
- ▶ Calibration function

Specifications

Model	ET-931		
	Measuring Range	Accuracy	Resolution
Humidity	0~100%RH	40~60%RH: ±2.0%RH	0.1
		20~40%RH: ±3.0%RH	
		60~80%RH: ±3.0%RH	
		0~20%RH: ±4.0%RH	
		80~100%RH: ±4.0%RH	
Temperature	-20°C~70°C -4°F~158°F	-20~70°C/-4~158°F ±1.0°C/1.8°F	0.1°C/°F
Dew Point Temp.	-20°C~70°C -4°F~158°F	-20~70°C/-4~158°F ±1.0°C/1.8°F	0.1°C/°F
Response time	1second		
Sampling rate	1time/second		
Operating Conditions	-20~60°C/-4°F~140°F;<90%RH(Non-condensation)		
Storage Conditions	-30~70°C/-22°F~158°F;<70%RH		
Dimension	185*66*33mm		
Weight	151g		



Accessories: User's Manual, Humidity and Temp Probe, Battery, carrying pouch, gift box

Professional Humidity & Temperature Meter ET-951



FEATURES

- ▶ Humidity and Temperature measuring
- ▶ Dew Point temperature
- ▶ Calibration function
- ▶ User selectable units
- ▶ Data hold
- ▶ Large backlit LCD display

Specifications

Model	ET-951		
	Measuring Range	Accuracy	Resolution
Humidity	0~100%RH	40~60%RH: ±2.0%RH	0.1
		20~40%RH: ±3.0%RH	
		60~80%RH: ±3.0%RH	
		0~20%RH: ±4.0%RH	
		80~100%RH: ±4.0%RH	
Temperature	-35°C~100°C -31°F~212°F	-35~10°C/31~14°F; ±1.0°C/1.8°F -10~70°C/14~158°F; ±0.5°C/0.9°F 70~100°C/158~212°F; ±0.5°C/0.9°F	0.1°C/°F
Dew Point Temp.	-35°C~100°C -31°F~212°F	25°C, 40~100%RH; ±1.0°C (±1.8°F)	0.1°C/°F
Response time	1second		
Sampling rate	1time/second		
Operating Conditions	-20~60°C/-4°F~140°F;<90%RH(Non-condensation)		
Storage Conditions	-30~70°C/-22°F~158°F;<70%RH		
Dimension(L*W*H)	261*66*33mm		
Weight	234g		



Accessories: User's Manual, Humidity and Temp Probe, Battery, carrying pouch, gift box