

### Mini Anemometer MT-905/905C

The anemometer is designed for air velocity and temperature measuring project, quality control, illness prevention and cure and all kinds of environmental air velocity and temperature measurement. It is widely used for the air velocity and temperature measurement at constructional engineering, factory, school, supermarket and household, etc.



#### FEATURES

- ▶ Max/Min reading hold
- ▶ User selectable units
- ▶ Low battery indication
- ▶ Auto power off

#### Specifications

Model	MT-905	MT-905C
Air Velocity Range	0.4m/s~30.0m/s	
	1.4~108 Km/h	
	0.9~67.0 MPH	
	0.8~58.0 knots	
	N/A	80~5900 ft/min
Temperature Range	N/A	-30~60°C/-22~140°F
Temperature Accuracy	N/A	±1.5°C/2.7°F
Operating Conditions	-20~60°C/-4~140°F;<90RH%(Non-condensation)	
Storage Conditions	-30~70°C/-22~158°F;<75 RH%	
Air Velocity Accuracy	±(3%+0.3 m/s)	
Air Velocity Resolution	0.1 m/s	
Sampling Time	1 time/ second	
Dimension(L*W*H)	175*55*38mm	
Weight	149g	



### Mini Thermo Anemometer MT-915



#### FEATURES

- ▶ Selectable measurement units: m/s,ft/min,Mph,km/hr or Knots
- ▶ Fast sampling rate
- ▶ Color LCD display with backlight
- ▶ MAX/MIN/DATA HOLD
- ▶ Over range indication, Low Battery indication
- ▶ Enable/disable auto power off



#### Specifications

Model	MT-915		
	Range	Resolution	Accuracy
Air Velocity Range	0.4 ~ 30.0 m/s	0.1	±( 3% + 0.3 m/s )
	1.4 ~ 108 Km/h	0.1	±( 3% + 1.0 Km/H )
	0.9 ~ 67.0 Mph	0.1	±( 3% + 0.4 Mph )
	0.8 ~ 58.0 Knots	0.1	±( 3% + 0.4 Knots )
	80 ~ 5900 ft/min	1.0	±( 3% + 40 ft/min )
Temperature Range	-20°C ~ 70°C / -4°F ~ 158°F		
Temperature Accuracy	±1.5°C / 2.7°F		
Temperature Resolution	0.1		
Operating Conditions	-20°C ~ 60°C, -4°F ~ 140°F, 10%RH ~ 90%RH		
Storage Conditions	-20°C ~ 60°C, -4°F ~ 140°F, 10%RH ~ 75%RH		
Power Supply	3*1.5V "AAA" batteries		
Battery Life	Over 60hours		
Dimension(L*W*H)	178.5*56*30.5mm		
Weight	84g		